

Nippel | 4109

TÄTNING:

24° kona

Dimensioner enligt skiss är angivna i mm.



Art nr.	Gänga (mm)	Slang ID tum	Slang DN (mm)	För rör (mm)	P	CH	A	L	Antal
4109-0312	M12x1,5	3/16	5	6	7	12	20.7	10	<input type="text"/>
4109-0412	M12x1,5	1/4	6	6	7	12	20.9	10	<input type="text"/>
4109-0414	M14x1,5	1/4	6	8	7	14	21.9	10	<input type="text"/>
4109-0416	M16x1,5	1/4	6	10	7	17	22.9	11	<input type="text"/>
4109-0516	M16x1,5	5/16	8	10	7	17	22.9	11	<input type="text"/>
4109-0518	M18x1,5	5/16	8	10	7	19	23.9	11	<input type="text"/>
4109-0616	M16x1,5	3/8	10	12	7	17	23.5	11	<input type="text"/>
4109-0618	M18x1,5	3/8	10	15	7	19	24.5	11	<input type="text"/>
4109-0622	M22 x 1,5	3/8	10	15	7	22	25.5	12	<input type="text"/>
4109-0822	M22x1,5	1/2	12	15	7	22	26.1	12	<input type="text"/>
4109-0826	M26x1,5	1/2	12	18	7.5	27	27.1	12	<input type="text"/>
4109-1026	M26x1,5	5/8	16	18	7.5	27	27.1	12	<input type="text"/>
4109-1230	M30x2,0	3/4	19	22	7.5	30	30.1	14	<input type="text"/>

HYDRAULIKPRODUKTER | PRESSKOPPLINGAR | NIPPEL | 4109

4109-1636	M36x2,0	1"	25	28	7.5	36	32.1	14	<input type="text"/>
4109-2045	M45x2,0	1" 1/4	32	35	10.5	46	36.5	16	<input type="text"/>
4109-2452	M52x2,0	1" 1/2	38	42	11	55	39	16	<input type="text"/>